



Dear Customer;

Below is our door spec information for our stocking exterior door slabs. If you have any questions please feel free to contact your salesperson.

Tru Tech HD Steel Builders Series – 10 year warranty

<http://trutechdoors.com/catalog.html>

24 gauge galvanized construction / primed surface with rust inhibitors

Wood edge construction w/ 12" wood lock-block reinforcement

Polyurethane foam core / High definition panel profile

NEW DOOR SLAB HINGE SPECS / HEIGHT:

Door slab height 78-5/8"

Door slab Hinge spec / top 7-3/4" / middle 37-3/4" / Bottom 67-3/4"

Door slab Bore location / Top to center line 44-7/8" with 2-38" backset

Plastpro Fiberglass Series – Smooth and Woodgrain in stock

<http://www.plastproinc.com/fiberglass-door-features/Energy.html>

- 25 year warranty on Smooth

-Limited Lifetime warranty on Woodgrain

Reinforced fiberglass is unaffected by moisture and humidity. Will not rot, splinter or warp. Won't dent or delaminate.

NEW DOOR SLAB HINGE SPECS / HEIGHT:

Door slab height 78-5/8"

Door slab Hinge spec / top 7-3/4" / middle 37-3/4" / Bottom 67-3/4"

Door slab Bore location / Top to center line 44-7/8" with 2-38" backset

KBM BUILT UNIT R/O SIZES ONLY

DOOR SIZE	R/O	NEW R/O	R/O UNIT HEIGHT
	WIDTH	W/ SILL RISER	NO SILL RISER
2/6 SINGLE	32-1/2"	83"	82"
2/8 SINGLE	34-1/2"	83"	82"
3/0 SINGLE	38-1/2"	83"	82"
1/0 x 3/0 1 SIDELITE	52-1/2"	83"	82"
1/0 x 3/0 x 1/0 2 SIDELITES	65-1/2"	83"	82"
5/0 FIXED ACTIVE PATIO	64"	83"	82"
5/0 DOUBLE SWING PATIO	63"	83"	82"
5/4 FIXED ACTIVE PATIO	68"	83"	82"
5/4 DOUBLE SWING PATIO	67"	83"	82"
6/0 FIXED ACTIVE PATIO	76"	83"	82"
6/0 DOUBLE SWING PATIO	75"	83"	82"
9/0 TRIPLE FIXED ACTIVE FIXED	113-1/2"	83"	82"
ALL DOORS w/ 12" TRANSOM	X	96-1/2"	X
ALL DOORS W/ 14" TRANSOM	X	98-1/2"	X
ALL DOORS W/ 16" TRANSOM	X	100-1/2"	X

SINGLE DOOR



DOUBLE DOOR

